

EUROPEAN AIR SAFETY COUPLINGS



EA SAFETY COUPLING MALE THREADED

ND	Inch	Thread DIN 2999	Material	Weight/pc Kg	Reference
10	3/8"	R 3/8	Galvanized steel	0.19	EAMS010
15	1/2"	R 1/2	Galvanized steel	0.23	EAMS013
20	3/4"	R 3/4	Galvanized steel	0.24	EAMS019
25	1"	R 1	Galvanized steel	0.25	EAMS025
32	1.1/4"	R 1 1/4	Galvanized steel	0.25	EAMS032



Claw distance: 42 mm
Working pressure: 10 bar / 145 Psi
Profiled seal DIN 3489-D: NBR
Male thread EN 10226-1 / DIN 2999, BSPT

EA SAFETY COUPLING FEMALE THREADED

ND	Inch	Thread EN ISO 228-1	Material	Weight/pc Kg	Reference
10	3/8"	G 3/8	Galvanized steel	0.19	EAFS010
15	1/2"	G 1/2	Galvanized steel	0.19	EAFS013
20	3/4"	G 3/4	Galvanized steel	0.19	EAFS019
25	1"	G 1	Galvanized steel	0.23	EAFS025
32	1.1/4"	G 1 1/4	Galvanized steel	0.28	EAFS032



Claw distance: 42 mm
Working pressure: 10 bar / 145 Psi
Profiled seal DIN 3489-D: NBR
Female thread EN ISO 228-1, BSP

EA SAFETY COUPLING WITH SERRATED HOSE SHANK

ND	Inch	For hose mm	Material	Weight/pc Kg	Reference
10	3/8"	10.0	Galvanized steel	0.20	EASS010
13	1/2"	13.0	Galvanized steel	0.19	EASS013
19	3/4"	19.0	Galvanized steel	0.22	EASS019
25	1"	25.0	Galvanized steel	0.24	EASS025
32	1.1/4"	32.0	Galvanized steel	0.32	EASS032



Claw distance: 42mm
Working pressure: 10 bar / 145 Psi
Profiled seal DIN 3489-D: NBR
Assembly: saddle and worm drive clamps

EUROPEAN AIR SAFETY COUPLINGS



EA SAFETY COUPLING CAP

Material	Weight/pc Kg	Reference
Galvanized steel	0.31	EAKS

Claw distance: 42mm
Working pressure: 10 bar / 145 Psi
Profiled seal DIN 3489-D: NBR



EA SAFETY COUPLING - 3 WAY CONNECTION

Material	Weight/pc Kg	Reference
Galvanized steel	0.61	EAYS

Claw distance: 42 mm
Working pressure: 10 bar / 145 Psi
Profiled seal DIN 3489-D: NBR



SAFETY CLIP

Material	Weight/pc Kg	Reference
Stainless steel AISI 304	0.018	VLBVR2
Galvanized steel	0.018	VLBVS2



SEAL

PROFILED SEAL DIN 3489-D

Material	Colour	OD mm +0.1 / -0.2	ID mm	Height +0.2 / -0.1	Box pieces	Weight kg	Reference
NBR	black	34.0	20.0	11.0	50	0.006	EAX

